

May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

### **EARTHTONE STAINS**

### **SECTION I: IDENTIFICATION**

EZCHEM, Inc. 141 Railroad St., Suite 117 Canton, GA 30114 Emergency Telephone Number: I-800-535-5035 Telephone Number for Information: 770-479-1764

Product Name: Earthtone Stains (Formally 2X Acid Stains)
Product Use: Chemical stains for concrete and masonry

### **SECTION II: HAZARD IDENTIFICATION**

Signal Word: DANGER Hazard Classification:

Acute Toxicity, Oral, Catagory 4
Acute Toxicity, Dermal, Catagory 4

Serious Eye Damage/Irritation, Catagory I

Specific Organ Toxicity, Single Exposure, Catagory 2

Hazard Statements:

H302 - Harmful if swallowed

H312 - Harmful in contact with skin.

H318 - Causes serious eye damage.

H371 - May cause damage to organs (Kidney)

**Precautionary Statements:** 

P260 – Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P35 I – IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P330 – Rinse mouth.

P362 – Take off contaminated clothing and wash before reuse.

P501 - Dispose of contents/container to an approved waste disposal plant.

### SECTION III: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components:CAS No.Percentage %Hydrochloric Acid7647-01-04-8%

Sodium dichromate 10588-01-9

Hazard Pictograms:







2-10%



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

### **SECTION IV – FIRST AID MEASURES**

**General Information:** Immediately remove any clothing soiled by the product and launder before reuse.

After inhalation: Remove to fresh air immediatly. If breathing difficulty continues, Get Medical Help.

After skin contact: Immediately wash with water and soap and rinse thoroughly. If irritation develops, Get Medical Help.

After eye contact: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

After ingestion: DO NOT INDUCE VOMITING. Drink two glasses of water and Get Immediate

Medical Help. Never give anything by mouth to an unconcious person.

Most Important Symptoms and Effects:

**Acute:** Severe eye irritation. **Delayed:** Skin irritation.

### SECTION V – FIRE AND EXPLOSION HAZARD DATA

**Suitable Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media: None known.

Fire Hazard: Non-Flammable Explosion Hazard: Non-Explosive

Reactivity: May react with aluminum to produce flammable hydrogen gas.

**Products of Combustion:** Not Applicable

Special Hazards Arising from the Substance or Mixture: No further relevant information available. Special Remarks and Advice for Firefighters: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

### SECTION VI – ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment (See section VIII). Keep unprotected persons away.

Methods and material for containment and cleaning up:

**Spill Response:** Absorb with liquid-binding material (sand, diatomite, and universal binders.) Use neutralizing agent, such ass sodium bicarbonate.

**Waste Disposal:** Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

**Environmental precautions:** Do not allow to enter sewers.



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

### SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND STORAGE

#### Handling

**Precautions for safe handling:** Ensure good ventilation. Use, store and transfer only with acid resistant plastic containers, DO NOT USE aluminum or any other metal container.

**Additional Hazards:** Avoid contact with aluminum and other metals. Reactions with aluminum, particularly foil, may generate flammable hydrogen gas.

**Hygiene Measures:** Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing, launder before reuse. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

#### Storage

**Storage Conditions:** Use, store and transfer only with acid resistant plastic containers, DO NOT USE aluminum or any other metal container.

**Storage Area:** Store at room temperature. Keep containers tightly sealed.

**Incompatible Products and Materials:** Avoid contact with aluminum and other metals. Reactions with aluminum, particularly foil, may generate flammable hydrogen gas.

### **SECTION VIII – EXPOSURE CONTROL MEASURES**

#### **Exposure Limits:**

CAS 7647-011-1 Hydrochloric Acid

PEL 5 ppm / 7 mg/m³ (ceiling) TVL 2 ppm / 3 mg/m³ (ceiling)

Appropriate Engineering Controls: Local ventilation.

#### Personal Protective Equipment:







**Hand:** Wear gloves of adequate length to offer appropriate skin protection from splashes. Nitrile, Butyl and PVC gloves have been found to offer adequate protection for incidental contact.

Eye: Safety Glasses.

**Skin and Body:** Non-absorptive boots.

Respiratory: None required.

Additional Information: None.



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

# **SECTION IX – PHYSICAL/CHEMICAL CHARACTERISTICS**

Appearance Form: Liquid

Color: Various Colors Odor: Pungent; acidic

pH-value: |-2

Boiling Point/Boiling Range: ~212°F / 100°C

Freezing Point: NE Flash Point: None

**Auto Igniting:** Product is not self-igniting.

Vapor Pressure: NE

Vapor Density: 1.12-1.30 g/cm<sup>3</sup>

Viscosity: NA
Solubility: Soluble
Evaporation Rate: NE

Flammability: Non-Flammable

**Decomposition Temperature:** NE

### **SECTION X – REACTIVITY DATA**

Conditions to be avoided: No decomposition if used according to specifications.

Incompatible materials: Bases, amines, alkali metals, metals - especially aluminum, permanganates,

Fluorine, metal acetylides, hexalithium disilicide, and bleach.

Hazardous Decomposition Products: No dangerous decomposition products known,

**Reactivity:** Reacts with concrete.

Chemical Stability: Stable.

Possibility of Hazardous Reactions: NA

### **SECTION XI – TOXICOLOGICAL INFORMATION**

Acute toxicity: Harmful if swallowed, Harmful in contact with skin.

Likely Route of Exposure: Skin.

**Exposure Symptoms:** 

Eyes: Can cause severe irritation and eye damage.

**Skin:** Irritation and possible burns. May cause allergic reaction with some people. Avoid repeated contact

**Inhalation:** Caughing, sore throat, shortness of breath, irritation of mucous membrane.

**Ingestion:** Sore throat, abdominal pain, burning. May cause kidney damage.

Effects (Short-term, Long-term):

Immediate: Eye irritation. Delayed: Skin irritation.

Chronic: NA Carcinogenicity: No.

**Sensitization:** No sensitizing effects known.



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

### **SECTION XII - ECOLOGICAL INFORMATION**

**Aquatic toxicity:** No further relevant information available.

Persistence and Degradability: No further relevant information available.

Behavior in Environmental Systems:

Bioaccumulative Potential: No further relevant information available.

Mobility in Soil: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized.

Other Adverse Effects: None known.

### **SECTION XIII - DISPOSAL CONSIDERATIONS**

Recommendation: Do not allow product to reach waterways or storm sewers. Disposal must be made in accordance with local, state and federal regulations.

Recommended Cleansing Agent: Water. **Additional Information:** Refer to Section 8

## SECTION XIV - TRANSPORT INFORMATION

**UN-Number:** 1760

**UN Proper Shipping Name:** N.O.S., Hydrochloric Acid Transport Hazard Class: 8 Corrosive substances

Packing Group:

**Environmental Hazards:** None - Not a marine pollutant.

Additional Information: ORM-D Ground Transportation

Only for Containers of 5L or less.


Warning: Corrosive Substances Special Precautions for User:





# **SECTION XV - OTHER REGULATORY INFORMATION**

### NFPA Ratings (Scale 0-4)



Health: 2 Fire: 1\* Reactivity: 2 \*Material is nonflammable, however certain reactions may liberate flammable hydrogen gas



May be used to comply with OSHA's Hazard Communication Standard (HCS), 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

# **SECTION XVI - OTHER INFORMATION**

Last Updated: 7-7-15

**NOTE:** The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. End of SDS.